

510,998

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
23 October 2003 (23.10.2003)

PCT

(10) International Publication Number
WO 03/087226 A1

(51) International Patent Classification⁷: **C08L 79/08**,
101/00, C08K 13/04 // (C08L 101/00, 79/08) (C08L
79/08, 101:00) (C08K 13/04, 3:00, 7:04)

(74) Agents: **WINTER, Catherine, J. et al.**; Patent Counsel,
General Electric Company, 3135 Easton Turnpike (W3C),
Fairfield, CT 06828 (US).

(21) International Application Number: **PCT/US03/11141**

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG,
SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN,
YU, ZA, ZM, ZW.

(22) International Filing Date: **11 April 2003 (11.04.2003)**

(25) Filing Language: **English**

(26) Publication Language: **English**

(30) Priority Data:
2002-109570 **11 April 2002 (11.04.2002) JP**

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (*for all designated States except US*): **GEN-
ERAL ELECTRIC COMPAMY** [US/US]; 1 River Road,
Schenectady, NY 12345 (US).

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

(72) Inventors; and

Published:

— *with international search report*

(75) Inventors/Applicants (*for US only*): **CHOATE, Kim**
[US/JP]; Oakwood 403, 2-17-15, Akasaka, Minato-ku,
Tokyo 107-0000 (JP). **UCHIYAMA, Tatsuya** [JP/JP];
438-65 Yagioka, Moka-shi, Tochigi-ken 321-4337 (JP).
KINOSHITA, Tsutomu [JP/JP]; 2-23-20, Kamikoumagi,
Moka-shi, Tochigi-ken 321-4337 (JP).

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: **FILLER REINFORCED POLYETHER IMIDE RESIN COMPOSITION AND MOLDED ARTICLE THEREOF**

(57) **Abstract: Problem** To offer a suitable polyether imide resin composition for the plastic components for automobiles, domestic appliances or OA apparatus, equipment's for media where heat resistance, dimensional stability and fire retardancy is required. **Means for solving the problem** Filler reinforced polyether imide resin composition is characterized by containing (A) polyether imide resin, (B) thermoplastic resin, (C) fibrous reinforced filler and (D) Non-fibrous inorganic filler, wherein the amount of (A) polyether imide resin is 1 to 95% by weight, (B) thermoplastic resin: 1 to 95% by weight, (C) fibrous reinforced filler: 2 to 80% by weight, (D) Non-fibrous inorganic filler: 2 to 80% by weight, when total of (A) to (D) is 100% by weight. The filler reinforced polyether imide resin composition contains (A) polyether imide resin, (B) thermoplastic resin, (C) fibrous reinforced filler, (D) Non-fibrous inorganic filler and (E) alkali earth metal salts, wherein the amount of (A) polyether imide resin: 1 to 95% by weight, (B) thermoplastic resin: 1 to 95% by weight, (C) fibrous type reinforced filler: 2 to 80% by weight, (E) non-fibrous inorganic filler: 2 to 80% by weight, when total of (A) to (D) is 100% by weight, and (E) alkali earth metal salts are included in the amount of 0 to less than 5 parts by weight.



WO 03/087226 A1